

GV-LPR CAM 20A ANPR Camera



C FC

INTRODUCTION

The GV-LPR CAM gives a 570TVL high-contrast license plate recognition video to the GV-LPR software that identifies license plates. The camera features 24 high-efficient LEDs for an illumination range of 30 meters / 98.43 feet. The camera also features a weather-sealed IP66-compliant housing with the heater and blower inside.





KEY FEATURES

- Built-in powerful IR LED illuminator
- Built-in always-on blower
- Weatherproof (IP66 standard)
- Sun-shield

Specifications					
Models		GV-LPR CAM 20M EIA I	OC 12V	GV-LPR CAM 20M CCIR DC 12V	
Camera					
Sensor		1/3" B/W Exview CCD	1/3" B/W Exview CCD		
Resolution		570 TVL	570 TVL		
Video Standard		NTSC		PAL	
Min. Illumination	Color	N/A		N/A	
	B/W	N/A		N/A	
	IR ON	0 Lux		0 Lux	
Shutter Speed		Automatic, Fixed (1/60	Automatic, Fixed (1/60 ~ 1/100000; Deault 1/500)		
White Balance		AWB	AWB		
Image Setting		• • • • • • • • • • • • • • • • • • • •	Brightness, Contrast, Saturation, Sharpness, Gamma, White Balance, Flicker-less, Image Orientation, Shutter Speed		
IR LAMP					
LED Quantity		24 High-efficient LEDs	24 High-efficient LEDs		
IR Distance		18 m / 59.06 ft (optima	18 m / 59.06 ft (optimal)		
		20 ± 5m / 65.62 ± 16.40	20 ± 5m / 65.62 ± 16.40 ft		
Illumination View Angle		30°	30°		
Illuminator Life		25,000 hrs	25,000 hrs		

GV-LPR CAM 20A July 2, 2012



Lens				
Focal Length		10 ~ 120 mm		
Max. Aperture		1.6		
Mount		CS Mount		
Image Format		1/3"		
Operation	Focus	manual		
	Zoom	manual		
	Iris	DC		
Mechanical				
Lens Mounting		N/A		
Connectors	Power	DC Jack		
	Auto Iris	DC drive		
	TV-Out	BNC		
General				
Operating Temperature		Operation: -30 °C ~ 50 °C / -22 °F ~ 122 °F		
		Storage: -30 °C ~ 70 °C / -22 °F ~ 158 °F		
Heater		≤ 5 °C (ON), > 5 °C (OFF) ; 20W		
Power Source		12V DC		
Max. Power Consumption		30W (normal), 50W (heater on)		
Dimensions (L x W x H)		425.01 x 155 x 156.75 mm / 16.73 x 6.10 x 6.17 in (with sun shield)		
Weight		5 kg / 11.02 lb (with sun shield)		
Construction		Robust aluminum with weatherproof sun shield		
Regulatory				
Protection classification		IP66		

Note 1: GV-LPR CAM 10A comes with free GV-LPR software, and the supplied GV-USB Dongle will need to be inserted to run the software. Since the free GV-LPR Software is a Trial Edition, it can only capture the license plate images and does not support the license plate recognition function. Therefore, the word "Capture" will be displayed in the license plate recognition results. **Note 2**: All specifications are subject to change with notice.

GV-LPR CAM 20A July 2, 2012